

React Day 2

Agenda

- Modules
- Modifying Our React App
- Props

Important Vocabulary

Babel- JavaScript compiler that can translate elements into JavaScript.

JSX- An extension of JavaScript that merges the gap between HTML and JavaScript

React- JavaScript library created for dynamically creating User Interfaces.


Importing Modules

Please always include:

```
import React from 'react'
```

```
import ReactDOM from 'react-dom'
```

Virtual DOM



Let's Create an app!

In gitbash/terminal run:

- `npm i -g create-react-app` (might have to use `sudo`)
- `npx create-react-app testApp`
- `cd testApp`
- `npm start`

Open Your App in Visual Studio!

Make sure your terminal is also open and in the app's folder.

React rendering

Use ReactDOM.render(*item*, *location*);

Example:

```
ReactDOM.render(<h1>Hi</h1>,  
  document.getElementById('root'));
```

For now, our first argument will
contain JSX!
Location will use vanilla JS

General Rules of Thumb

- If you are embedding data use {data}
- Do **not** use quotes around the html you are rendering
 - “<h1>Words</h1>”
- When you return JSX, surround your text with parenthesis

Rendering with Functions

- More formally called “Functional Components”
- Functions **must** be “pure”

Pro tip: Use self closing tags for now! `<tag />`

Rendering with Classes

```
class ComponentName extends React.Component{}
```

Make sure you have a `render()` method, where you return the JSX you would like to use.

Props

Now, when we call our components we can pass data through the properties (props).

They are read only!

`<Item data = "Data"></Item>` or `<Item data = "Data" />`

WTWAW (What To Walk Away With)

- Be able to create and export a module
- Be able to render simple JSX
- Create a Functional Component
- Create a Class Component
- Use props to pass information